



# Mr Sheen fabric & carpet cleaner

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Issue date:20/08/2020

Revision date: 22/08/2022

Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Mr Sheen fabric & carpet cleaner  
Type of product : Cleaning agent  
Product code : SH749  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Supplier's details

##### Manufacturer

Shield Chemicals (Pty) Ltd  
9 London Rd  
Apex  
P.O. Box 1939  
1501 Benoni - South Africa  
T (011) 421 7111  
[info@shieldchem.co.za](mailto:info@shieldchem.co.za)

#### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS

Aerosol, Category 1 H222;H229  
Hazardous to the aquatic environment — Acute Hazard, Category 3 H402  
Full text of H statements : see section 16

#### 2.2. Label elements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



GHS02

Signal word (GHS-ZA) : Danger  
Hazardous ingredients : propane; butane, liquefied, under pressure; SAS; Sodium dodecyl sulphate  
Hazard statements (GHS-ZA) : H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H402 - Harmful to aquatic life  
Precautionary statements (GHS-ZA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P273 - Avoid release to the environment.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents and container to an approved waste disposal plant.

#### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Pressurised container: May burst if heated,Extremely flammable aerosol,Harmful to aquatic life

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	(CAS-No.) 106-97-8	5.0 - 10.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401

# Mr Sheen fabric & carpet cleaner

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Name	Product identifier	%	Classification according to the United Nations GHS
propane	(CAS-No.) 74-98-6	1.0 - 5.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified
SAS	(CAS-No.) 97489-15-1	1.0- 5.0	Acute Tox. 4 (Oral), H302 Aquatic Acute 2, H401
Sodium dodecyl sulphate	(CAS-No.) 151-21-3	1.0 - 5.0	Acute Tox. 5 (Dermal), H313 Aquatic Acute 3, H402 Aquatic Chronic Not classified

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Mechanically recover the product.  
Other information : Dispose of materials or solid residues at an authorized site.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

# Mr Sheen fabric & carpet cleaner

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

<b>propane (74-98-6)</b>	
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Propane
OEL TWA (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OEL TWA (ppm)	1000 ppm
Regulatory reference	Government Notice No. R 904
<b>butane, liquefied, under pressure (106-97-8)</b>	
<b>South Africa - Occupational Exposure Limits (Recommended Limits)</b>	
Local name	Butane
OEL TWA (mg/m <sup>3</sup> )	1430 mg/m <sup>3</sup>
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
OEL STEL (ppm)	750 ppm
Regulatory reference	Government Notice. R: 1179
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	n-Butane
OEL TWA (mg/m <sup>3</sup> )	1430 mg/m <sup>3</sup>
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
OEL STEL (ppm)	750 ppm
Regulatory reference	Government Notice No. R 904

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Colour : Off-white.  
Odour : characteristic.  
Odour threshold : No data available  
pH : 6 - 7  
pH solution : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Relative evaporation rate (ether=1) : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : Extremely flammable aerosol.  
Vapour pressure : No data available  
Vapour pressure at 50 °C : No data available  
Relative vapour density at 20 °C : No data available  
Relative density : No data available  
Relative density of saturated gas/air mixture : No data available

# Mr Sheen fabric & carpet cleaner

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosive limit (LEL)	: No data available
Upper explosive limit (UEL)	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>propane (74-98-6)</b>	
LC50 inhalation rat (ppm)	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
<b>butane, liquefied, under pressure (106-97-8)</b>	
LC50 inhalation rat (mg/l)	1442.738 - 1443 mg/l 15 MIN
LC50 inhalation rat (ppm)	800000 ppm 15 MIN
<b>Sodium dodecyl sulphate (151-21-3)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
<b>SAS (97489-15-1)</b>	
LD50 oral rat	500 - 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

Skin corrosion/irritation	: Not classified pH: 6 - 7
Serious eye damage/irritation	: Not classified pH: 6 - 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

# Mr Sheen fabric & carpet cleaner

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

<b>Mr Sheen fabric &amp; carpet cleaner</b>	
Vaporizer	Aerosol

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>propane (74-98-6)</b>	
LC50 fish 1	24 mg/l (96 h, Pisces, Literature study)
LC50 fish 2	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 Daphnia 1	7 mg/l (48 h, Daphnia magna, Literature study)
BCF fish 1	9 - 25 (Pisces, QSAR)
Log Pow	1.09 - 2.8 (Experimental value, 20 °C)

<b>butane, liquefied, under pressure (106-97-8)</b>	
LC50 fish 1	> 1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h algae (1)	5.3 - 5.5 mg/l (Algae, QSAR)
Log Pow	2.89 (Experimental value)

<b>Sodium dodecyl sulphate (151-21-3)</b>	
LC50 fish 1	29 mg/l Test organisms (species): Pimephales promelas
EC50 other aquatic organisms 1	11.1 mg/l Test organisms (species): other aquatic crustacea:Pseudosida ramosa
EC50 72h algae (1)	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h algae (2)	53 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC chronic fish	>= 1.357 mg/l Test organisms (species): Pimephales promelas Duration: '42 d'

<b>SAS (97489-15-1)</b>	
LC50 fish 1	5.5 mg/l Test organisms (species): Leuciscus idus melanotus
LC50 fish 2	8.4 mg/l Test organisms (species): Leuciscus idus melanotus
EC50 Daphnia 1	9.2 mg/l Test organisms (species): Daphnia magna
EC50 Daphnia 2	9.8 mg/l Test organisms (species): Daphnia magna
EC50 72h algae (1)	> 61 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h algae (2)	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	1.6 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

#### 12.2. Persistence and degradability

<b>Mr Sheen fabric &amp; carpet cleaner</b>	
Persistence and degradability	No additional information available

<b>propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>butane, liquefied, under pressure (106-97-8)</b>	
Persistence and degradability	Readily biodegradable in water.

#### 12.3. Bioaccumulative potential

<b>Mr Sheen fabric &amp; carpet cleaner</b>	
Bioaccumulative potential	No additional information available

<b>propane (74-98-6)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>butane, liquefied, under pressure (106-97-8)</b>	
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### 12.4. Mobility in soil

<b>Mr Sheen fabric &amp; carpet cleaner</b>	
Mobility in soil	No additional information available

# Mr Sheen fabric & carpet cleaner

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

<b>propane (74-98-6)</b>	
Surface tension	0.016 N/m (-47 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).

<b>butane, liquefied, under pressure (106-97-8)</b>	
Surface tension	< 0.1 N/m (0 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).

### 12.5. Other adverse effects

Ozone : Not classified  
 Other adverse effects : No additional information available




## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. Proper Shipping Name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		 Not applicable
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available		

### 14.6. Special precautions for user

#### - SANS

Special provisions (SANS) : 63, 190  
 Limited quantities (SANS) : See SP277  
 Limited quantities (SANS) : See SP277  
 Packagings, large packagings and IBCs : P003  
 Packing instructions (SANS)  
 Packagings, large packagings and IBCs Special : PP17, PP87  
 packing instructions (SANS)

#### - IMDG

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
 Packing instructions (IMDG) : P207, LP200  
 Special packing provisions (IMDG) : PP87, L2  
 EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
 EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
 Stowage category (IMDG) : None

#### - IATA

PCA Excepted quantities (IATA) : E0  
 PCA Limited quantities (IATA) : Y203  
 PCA limited quantity max net quantity (IATA) : 30kgG

# Mr Sheen fabric & carpet cleaner

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

## SECTION 16: Other information

Issue date : 20/08/2020

Revision date : 22/08/2022

Full text of H-statements:

H220	Extremely flammable gas.
H227	Combustible liquid
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

SDS South Africa

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*